

STROBES

A broad range of strobe lights is available offering the customer a variety of colours, styles and voltages. Combined strobe sounder units are also available and can be used to reduce installation cost and time.



Strobes utilise flashing Xenon beacons that make effective replacements for sounders in areas of high ambient noise or where people with hearing difficulties are present. They are also useful in situations where a loud noise might cause panic e.g. Staff alarms in a nightclub.

BASIC RANGE

STR6000 This is a multipurpose strobe that incorporates Surge Current Suppression circuitry. This prevents fuses blowing without the need for heavy-duty power supplies. The STR6000 is suited to most circumstances and weatherproof when used with a deep or 'U' base. The 'U' base enables surface wiring.

ESST A high output, multipurpose sounder-strobe unit that combines the features of the ES4000 sounder with an integral 1W strobe. With its subtle styling and low power requirement, this unit is most suited to residential situations that call for a sound and visual output.

STR2 A low profile 2W strobe that is waterproof and ideal for panel mounting.

FEATURES

- Wide choice
- Durable and smart designs
- Reduced power consumption
- High outputs
- Built in terminal blocks
- Weatherproof versions available

For information on the wider range of colours, styles and voltages available please contact sales on 01291 431910

SPECIFICATION

	STR2	STR6000	ESST
Voltage	24V DC	24V DC	24V DC
Flash rate	1 Hz (60 per min)	1 Hz (60 per min)	1 Hz (60 per min)
Flash energy	-	1.45j	0.7j
Operation	Continuously rated	Continuously rated	Continuously rated
Current consumption	55mA	90mA	68mA
Tube power rating	2W	2.1W	1W
Line monitoring	Not suitable	Polarised	Polarised
Operating temp	-20°C to +55°C	-20°C to +55°C	-10°C to +55°C
Ingress protection	IP65	IP54 - S* base IP65 - D/U* base	IP54 - S base IP65 - D/U base
Weight	0.2kg	0.2kg	0.2kg
Depth	45mm	75mm - S base 103mm - D/U base	89mm - S base 117mm - D/U base
Base diameter	77mm	93mm	93mm
Mounting	Panel Mount	Surface/Flush	Surface/Flush
Lens colour options	Red, Clear, Amber, Green, Blue		
Base options	None	Shallow, Deep, Deep lockable, 'U', 'U' lockable	

* S = Shallow base (for flush mounting)

* D/U = Deep or 'U' base

NB For sounder specification see relevant information sheet

ORDER CODES

CODE	DESCRIPTION
STR6000	2.1W high profile strobe
ESSTFR	1W Strobe and 93dBA sounder, Shallow base, red
ESSTSR	1W Strobe and 93dBA sounder, Deep base, *w.proof, red
ESSTUR	1W Strobe and 93dBA sounder, 'U' base (for surface wiring),w.proof, red
ESSTFW	1W Strobe and 93dBA sounder, Shallow base, white
ESSTSW	1W Strobe and 93dBA sounder, Deep base, w.proof, white
ESSTUW	1W Strobe and 93dBA sounder, 'U' base (for surface wiring),w.proof, white
STR2	2W low profile panel mount strobe

*w.proof = weatherproof

Other colours, styles and voltages available

PLEASE NOTE: The standard STR6000 may also be linked to an ES6000CW 93dBA ceiling sounder to form a combined unit